

Wireless Siren/Flash Actuator

Product ref.: 84392
PRODUCT FEATURES



- Enables triggering of signalling devices in alarm system via radio-controlled commands
- Activation of a 12 V siren and a 12 V flashing light
- Preset statutory signal duration for flashing light and siren
- Jet-proof (IP65), suitable for outdoor application
- Internal tamper contact provides tamper protection
- Internal battery status monitoring, deep discharge protection and protection against polarity reversal
- All Homematic transmitters can be connected
- Back-up supply via lead gel battery

TECHNICAL SPECIFICATIONS

Supply voltage:	230 V/50 Hz
Current consumption:	30 mA (max.)
Switching outputs:	2x 12 VDC, total load 1 A max.
Back-up supply:	Lead gel battery, 12 V/1.2 Ah
Degree of protection:	IP65
Operating temperature:	-10 to +50 °C
Dimensions (W x H x D):	160 x 160 x 90 mm
Weight:	692 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	300 m

LOGISTIC DATA

Product reference:	84392
EAN code:	4047976843923
Short description:	HM-Sec-SFA-SM
Packing unit:	10
Packaging dimensions:	184 x 281 x 97 mm
Total weight:	1596.0 g

PACKAGE CONTENTS

Wireless Siren/Flash Actuator
Lead gel battery, 12 V/1.2 Ah
Mounting materials (5x screws, 5x plugs, 1x sealing ring)
Operating manual in DE and EN